

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION						
NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special-0			HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B			
Manufactured For: AmSan			DOT Hazard Classification: ORM-D			
Address: Three Parkway North, Suite 120N Deerfield, IL 60015			Identity (trade name as used on label): RENOWN WATERBASED STAINLESS STEEL CLEANER			
Phone: 1-847-607-2300			MSDS Number: A00142		Revision- 11	
EMERGENCY RESPONSE NUMBER: 1(800)255-3924			Date Prepared: 02/23/00		Prepared By: LF/CH	
NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA			Information Calls: (770)422-2071			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
PETROLEUM SOLVENT		64742-54-7	No	5mg/m3	5mg/m3	d
PETROLEUM DISTILLATE		8052-41-3	No	100	100	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A			Specific Gravity (H2O=1): Concentrate Only = 0.908			
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E			Evaporation Rate (BuAc = 1): N/E			
Solubility in Water: Soluble			Water Reactive: No			
Appearance and Odor: White foam with light lemon fragrance.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE		Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E			
FLASH POINT AND METHOD USED (non-aerosols): N/A			EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE			HAZARDOUS POLYMERIZATION <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizers.			Conditions to Avoid: Open flame, welding arcs, heat.			
Hazardous Decomposition Products: CO, CO2.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input checked="" type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Mild irritation.			Skin Contact: May aggravate existing skin conditions.			
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause headaches, dizziness and nausea.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in a positive pressure mode.						
Protective Gloves: Latex if skin easily irritated.			Eye Protection: Safety glasses recommended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb spilled liquid with suitable medium. Place in closed drum for proper disposal. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH LIQUID TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only
THIS MSDS IS CURRENT AS OF March 14, 2003. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.